



Properties

| | |
|-------------------|-------------------|
| Base Construction | Die Cast Aluminum |
| Lens | Glass |
| Application | Sconce |
| Location | Wet |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | Bronze |
| CCT | 5000K |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|-----|-------------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K/5700K |
|-----|-------------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|---------------------------|-----------------------|---|-----------------------------------|
| DSKD-14 | W:14.12" H:9" E:11.25" | 12/24/36/4 8/60/72 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1560/3120/4680/624 0/7800/9360 |

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com