



Properties	
Base Construction	Steel
Lens	Glass
Application	Sconce
Location	Damp, Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection	
Voltage	120V (non dimming)
Finish	ORB
CCT	4000K

CCT Options

Finish Options

☐ Brushed Nickel

 \square Black

 \square Bronze

CCT 2700K/3000K/3500k/4000K/5000K

☐ Gold/Brass

 \square ORB

 $\ \square$ White





Options

Size	Dimensions	Wattage	Voltage	Lumens
VBDSAW-12	W:4.8" H:12"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600

Size	Dimensions	Wattage	Voltage	Lumens
VBDSAW-24	W:4.8" H:24"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
VBDSAW-31	W:4.8" H:31"	25/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/3900/5200

Options

BBX-Backbox W

3/4" Conduit hole

EMG - Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com