







Properties

| Properties | | |
|--------------------|-------|--------------------|
| Base Construction | | Die Cast Aluminum |
| Lens | | Polycarbonate |
| Application | | Sconce |
| Location | | Wet |
| CRI | | 80 |
| Life Hours | | 50,000 |
| Light Source | | Integrated LED |
| Standard Selection | | |
| Voltage | | 120V (non dimming) |
| Finish | | Black |
| CCT | | 3000K |
| Finish Options | | |
| □ Black | □ ORB | |

CCT Options

☐ Gold/Brass

☐ Brushed Nickel

CCT 2700K/3000K/3500k/4000K/5000K

□ White

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|--------------|-----------------|---|--------------------|
| WCWH-11 | W:7" H:11.3" | 10/15/20/2 5 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/2600/325 |

Options

EMG - Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com