



ADA Compliant

### Properties

|                   |                |
|-------------------|----------------|
| Base Construction | Aluminum       |
| Lens              | Glass          |
| Application       | Address        |
| Location          | Wet            |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

### Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | ORB                     |
| CCT     | 3000K                   |

### Finish Options

- |                                         |                                     |
|-----------------------------------------|-------------------------------------|
| <input type="checkbox"/> Black          | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze         | <input type="checkbox"/> ORB        |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White      |

### CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

### Options

| Size    | Dimensions              | Wattage | Voltage                                                                                                           | Lumens |
|---------|-------------------------|---------|-------------------------------------------------------------------------------------------------------------------|--------|
| NB129-6 | H:6.3" W:6.3"<br>E:3.8" | 9       | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1170   |

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)