



ADA Compliant

## Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Glass             |
| Application       | Address           |
| Location          | Damp              |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

## Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | ORB                     |
| CCT     | 3000K                   |

## Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

## CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

## Options

| Size     | Dimensions           | Wattage | Voltage                                                                                                           | Lumens |
|----------|----------------------|---------|-------------------------------------------------------------------------------------------------------------------|--------|
| NB134-10 | H:10" W:5"<br>E:3.9" | 9       | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1170   |

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)