



ADA Compliant

## Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Glass             |
| Application       | Address           |
| Location          | Wet               |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

## Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | Black                   |
| CCT     | 3000K                   |

## Finish Options

|   |                                     |
|---|-------------------------------------|
| <input type="checkbox"/> Black          | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze         | <input type="checkbox"/> ORB        |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White      |

## CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500K/4000K/5000K |
|-----|-------------------------------|

## Options

| Size     | Dimensions     | Wattage | Voltage   | Lumens |
|----------|----------------|---------|---|--------|
| NB143-12 | W:5.5" H:11.8" | 9       | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1170   |

Not seeing what you're looking for?

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)