



ADA Compliant

### Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Acrylic           |
| Application       | Address           |
| Location          | Wet               |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

### Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | Black/Maple             |
| CCT     | 3000K                   |

### Finish Options

- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White
- Black/Maple

### CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

### Options

| Size     | Dimensions           | Wattage | Voltage                                                                                                         | Lumens |
|----------|----------------------|---------|-----------------------------------------------------------------------------------------------------------------|--------|
| NB145-15 | H:14.5" W:8"<br>E:4" | 10      | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300   |

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)