# BCJBW12

Sconce



ADA Compliant

## Properties

| | |
|---|---|
| Base Construction | Aluminum |
| Lens | Acrylic |
| Application | Sconce |
| Location | IP65, Wet |
| CRI | >80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

## Standard Selection

| | |
|---|---|
| Voltage | 120-277 |
| Finish | Black |
| CCT | 3000K |

## Finish Options

- ☐ Black
- ☐ Bronze
- ☐ Gold/Brass
- ☐ ORB
- ☐ White
- ☐ Satin Nickel

## CCT Options

| | |
|---|---|
| CCT | 3000K |

## Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---|---|---|---|---|
| BCJBW-10 | W:7" H:10" E:3" | 10/15/20 | 120-277 / ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1300/1950/2600 |
| BCJBW-15 | W:7" H:15" E:4" | 15/20/25 | 120-277 / ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1950/2600/3250 |
| BCJBW-18 | W:7" H:18" E:4" | 20/25/30 | 120-277 / ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3250/3900 |
| BCJBW-24 | W:7" H:24" E:4" | 20/25/30 | 120-277 / ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3250/3900 |
| BCJBW-30 | W:9" H:30" E:4" | 20/25/30 | 120-277 / ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3250/3900 |
| BCJBW-42 | W:9" H:42" E:4" | 30/35/40 | 120-277 / ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 3900/4550/5200 |

## Options

BBX-Backbox W
¾” Conduit hole
EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming
PC - Photo Control

**Not seeing what you're looking for?**

Contact us!

info@asllighting.com

© Copyright © 2026 ASL Lighting Inc. All rights reserved. • asllighting.com