BSBW

Sconce

ADA Compliant

Properties

Base Construction	Stainless Steel
Lens	Acrylic
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	2700K

Finish Options

- ☐ Black
- ☐ Bronze
- ☐ Brushed Nickel
- ☐ Gold/Brass
- ☐ ORB
- ☐ White

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
BSBW-12	H:12" W:6" E:4"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
BSBW-15	H:15" W:6" E:4"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
BSBW-18	H:18" W:6" E:4"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BSBW-24	H:24" W:6" E:4"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BSBW-30	H:30" W:6" E:4"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BSBW-42	H:42" W:6" E:4"	30/35/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3900/4550/5200

Options

BBX-Backbox W
¾” Conduit hole
EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming
PC - Photo Control

Not seeing what you're looking for?

Contact us!

info@asllighting.com

© Copyright © 2026 ASL Lighting Inc. All rights reserved. • asllighting.com