



### Properties

Base Construction	Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	2700K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

CCT	2700K/3500k/4000K/5000K
-----	-------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
BSK-15	H:15" W:9" E:4"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming ) / DVD (120V-277V 0-10 dimming )	1300/1950/2600
BSK-18	H:18" W:9" E:4"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming ) / DVD (120V-277V 0-10 dimming )	1300/1950/2600
BSK-26	H:26" W:9" E:4"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DVD (120V-277V 0-10 dimming )	1950/2600/3250

### Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)