



### Properties

Base Construction	Aluminum
Lens	Silicon
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	300

### Standard Selection

Voltage	120V-277V 0-10 dimming
Finish	Black
CCT	3000K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

CCT	3000K/4000K/5000K
-----	-------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
C2116-12	H:0.7" L:11.8" W:11.8"	50	DVD (120V-277V 0-10 dimming )	6500
C2116-16	H:0.7" L:15.7" W:15.7"	60	DVD (120V-277V 0-10 dimming )	7800
C2116-20	H:0.7" L:19.7" W:19.7"	90	DVD (120V-277V 0-10 dimming )	11700
C2116-35	H:0.7" L:35.4" W:19.7"	125	DVD (120V-277V 0-10 dimming )	16250
C2116-43	H:0.7" L:43.3" W:25.6"	150	DVD (120V-277V 0-10 dimming )	19500

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)