



Properties

Base Construction	Aluminum
Lens	Polycarbonate
Application	Flush Mount
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	3000K

Finish Options

- | | |
|---|-------------------------------------|
| <input type="checkbox"/> Black | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze | <input type="checkbox"/> ORB |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White |

CCT Options

CCT	3000K/4000K/5000K
-----	-------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2127-12	D:11.8" H:2.6"	15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950
C2127-16	D:15.7" H:2.6"	20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600
C2127-20	D:18.9" H:3.7"	25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250
C2127-24	D:23.6" H:3.7"	40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	5200
C2127-35	D:35.4" H:3.7"	90	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	11700
C2127-47	D:47.2" H:3.7"	150	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	19500

Not seeing what you're looking for?

Contact us!

info@asllighting.com