



### Properties

Base Construction	Aluminum
Lens	Polycarbonate
Application	Recessed Ceiling Fixture
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	120

### Standard Selection

Voltage	120V-277V 0-10 dimming
Finish	Black
CCT	3000K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

CCT	3000K/4000K/5000K
-----	-------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
C2128-20	D:20" H:3.7"	25/30	DVD (120V-277V 0-10 dimming )	3250/3900
C2128-25	D:24.8" H:3.7"	25/40	DVD (120V-277V 0-10 dimming )	3250/5200
C2128-37	D:36.3" H:3.7"	90	DVD (120V-277V 0-10 dimming )	11700
C2128-48	D:48" H:3.7"	150	DVD (120V-277V 0-10 dimming )	19500

### Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)