



### Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K
-----	--

### Options

Size	Dimensions	Wattage	Voltage	Lumens
CCC40-10	H:4" L:10.5" W:10.5"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
CCC40-13	H:4" L:13" W:13"	10/15/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/3250
CCC40-16	H:6" L:16" W:16"	15/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250
CCC40-19	H:6" L:19" W:19"	15/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250

### Options

- BBX-Backbox W
- ¾" Conduit hole
- EMG - Emergency
- EMG+BBX-Emergency + Backbox W
- ¾" Conduit hole
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)