









Properties		
Base Construction	Steel	
Lens	Acrylic	
Application	Vanity	
Location	Damp	
CRI	80	
Life Hours	50,000	
Light Source	Integrated LED	
Standard Selection		
Voltage	120V (non dimming)	
Finish	Black	
CCT	2700K	
Finish Options		
□ Black	□ Gold/Brass	
□ Bronze	□ ORB	
☐ Brushed Nickel	□ White	
CCT Options		
CCT	2700K/3000K/3500k/4000K/5000K	

## Options

Size	Dimensions	Wattage	Voltage	Lumens
CCV28	L:25", 37", 49" H:5.37"	15/20/25/3 0/40	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250/390 0/5200
CCV28-25	L:25" H:5.37"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250
CCV28-37	L:37" H:5.37"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
CCV28-49	L:49" H:5.37"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3900/5200

Not seeing what you're looking for?

Contact us!

info@asllighting.com