



### Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Pendant
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V Triac dimming
Finish	Black
CCT	2700K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

CCT	2700K/3000K/3500k/4000K
-----	-------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
CVBH-22	H:4.8" L:22" W:2.75" MH:60"	11/15/22	TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1430/1950/2860
CVBH-34	H:4.8" L:34" W:2.75" MH:60"	18/25	TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2340/3250
CVBH-46	H:4.8" L:46" W:2.75" MH:60"	22/30/40	TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2860/3900/5200

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)