



Properties

Base Construction	Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	2700K

Finish Options

- Black
- Gold/Brass
- Bronze
- ORB
- Brushed Nickel
- White

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
DSBV-18	H:5.5" L:18.5" E:3.25"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
DSBV-24	H:5.5" L:24.5" E:3.25"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
DSBV-36	H:5.5" L:36.5" E:3.25"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
DSBV-48	H:5.5" L:48.5" E:3.25"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200

Not seeing what you're looking for?

Contact us!

info@asllighting.com