



### Properties

|                   |                |
|-------------------|----------------|
| Base Construction | Aluminum       |
| Lens              | Polycarbonate  |
| Application       | Sconce         |
| Location          | Wet            |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

### Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | Black                   |
| CCT     | 3000K                   |

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

|     |                   |
|-----|-------------------|
| CCT | 3000K/4000K/5000K |
|-----|-------------------|

### Options

| Size    | Dimensions               | Wattage  | Voltage                      | Lumens         |
|---------|--------------------------|----------|------------------------------|----------------|
| DSKA-8  | H:8.1" W:6.5"<br>E:3.85" | 21/28/35 | DV (120V-277V (non dimming)) | 2730/3640/4550 |
| DSKA-12 | H:12.4" W:5.9"<br>E:9.9" | 45/60/75 | DV (120V-277V (non dimming)) | 5850/7800/9750 |

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)