



Properties

Base Construction	Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	2700K

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

CCT 2700K/3000K/5000K/3CCT - 3000K / 3500K / 4000K/5CCT - 2700K / 3000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
HRPC-11	D:11" H:3.7"	10/17	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2210
HRPC-14	D:14" H:3.9"	15/24	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3120
HRPC-19	D:18.9" H:3.9"	15/25/35	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/4550

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com