



Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	2700K

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
OBY-24	H:5.7" L:24.5" E:4.5"	15/23	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990
OBY-36	H:5.7" L:36.5" E:4.5"	25/36	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/4680
OBY-48	H:5.7" L:48.5" E:4.5"	25/35/46	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/4550/5980

Not seeing what you're looking for?

Contact us!

info@asllighting.com