



Properties

| | |
|-------------------|---|
| Base Construction | Die-formed Cold-rolled Steel and Aluminum Extrusion |
| Lens | Glass |
| Application | Mini Pendant |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|------------------------|
| Voltage | 120V-277V 0-10 dimming |
| Finish | Black |
| CCT | 2700K |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|--------|-------------------------|---------|---|--------|
| RFDJ-5 | D:4.8" H:7.8" MH:72" | 14 | DVD (120V-277V 0-10 dimming) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) | 1820 |
| RFDJ-6 | D:6" H:9.1" MH:72" | 17 | DVD (120V-277V 0-10 dimming) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) | 2210 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com