



### Properties

Base Construction	Steel, Cold-rolled Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	UP AND DOWN

### Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	2700K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
TLBF-10	H:4.5" W:9.8" E:4"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
TLBF-12	H:3.5" W:12" E:4"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
TLBF-24	H:3.5" W:24" E:4"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
TLBF-36	H:3.5" W:36" E:4"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900

### Options

- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)