© Copyright © 2026 ASL Lighting Inc. All rights reserved. • asllighting.com

© Copyright © 2026 ASL Lighting Inc. All rights reserved. • asllighting.com



Properties

Base Construction	Steel
Lens	Glass
Application	Sconce
Location	IP65, Wet
CRI	>80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120-277
Finish	Black
CCT	3000K

Finish Options

- ☐ Black
- ☐ Bronze
- ☐ Gold/Brass
- ☐ ORB
- ☐ White
- ☐ Satin Nickel

CCT Options

CCT	3000K

© Copyright © 2026 ASL Lighting Inc. All rights reserved. • asllighting.com

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBDSAW-12	W:4.8" H:12" E:4.2"	10/15/20	120-277 / ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
VBDSAW-24	W:4.8" H:24" E:4.2"	15/20/25	120-277 / ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
VBDSAW-31	W:4.8" H:31" E:4.2"	25/30/40	120-277 / ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/3900/5200

Options

BBX-Backbox W
¾” Conduit hole
EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com

© Copyright © 2026 ASL Lighting Inc. All rights reserved. • asllighting.com