



### Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	3CCT - 3000K / 3500K / 4000K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

CCT	3CCT - 3000K / 3500K / 4000K
-----	------------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
VBEA-25	H:4.4" L:25.5" E:3.8"	10/17/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2210/2600
VBEA-37	H:4.4" L:37.3" E:3.8"	15/24/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3120/3250
VBEA-49	H:4.4" L:49.1" E:3.8"	20/25/36	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/4680

### Options

- BBX-Backbox W
- ¾" Conduit hole
- EMG - Emergency

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)