



ADA Compliant

### Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V (non dimming)
Finish	Black
CCT	3CCT - 3000K / 3500K / 4000K

### Finish Options

- |   |                                     |
|---|-------------------------------------|
| <input type="checkbox"/> Black          | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze         | <input type="checkbox"/> ORB        |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White      |

### CCT Options

CCT	3CCT - 3000K / 3500K / 4000K
-----	------------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
VBJH-22	H:4.3" L:22" E:2.9"	23	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2990
VBJH-34	H:4.3" L:34" E:2.9"	35	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	4550
VBJH-46	H:4.3" L:46" E:2.9"	50	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	6500

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)