VBRD24

Vanity



ADA / BAA / CSA

Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	>80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120-277
Finish	Black
CCT	3000K

Finish Options

- ☐ Black
- ☐ Bronze
- ☐ Gold/Brass
- ☐ ORB
- ☐ White
- ☐ Satin Nickel

CCT Options

CCT	3000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBRD-27	W:27" H:5" E:2.5", 3.5"	15/20/25	120-277 / ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
VBRD-37	W:37" H:5" E:2.5", 3.5"	20/25/30	120-277 / ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900

Options

BBX-Backbox W
¾" Conduit hole
EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com

© Copyright © 2026 ASL Lighting Inc. All rights reserved. • asllighting.com