



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:					ACCESSORIES:				
PROJECT:					NOTES:				
TYPE:					AREA:				

FEATURES

PRODUCT IMAGE

- APPLICATION**
Outdoor
Sconce
Wet
- LOCATION**
Wet



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

3500K
NEUTRAL

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED LG/NICHIA/SAMSUNG	TESTED LM80 AND LM82	CRI 80+	LIFE HOURS 50,000
--	-----------------------------------	-------------------	-----------------------------

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
15	1600	1010
20	2400	1400

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
Stainless Steel

STANDARD LENS
Opal Acrylic

STANDARD FINISH
Bronze

MODEL #BCJC ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W15 - 15 W20 - 20	Standard Voltage: ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE TD - 120V TRIAC/ELV DIMMABLE DVD - 120/277V 0-10V DIMMABLE	 27K  30K  35K  40K  50K	H18 - H18 X W8 X E4 H8 - H8 X W8 X E4

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control	BB - Back Box (Extended Base) BBX - Back Box (Extended Base) (Conduit Holes Optional) FUS - Fused

CUSTOM FINISH OPTIONS				
 FGB Gloss Black	 FGBR Gloss Brass	 FGW Gloss White	 FMB Matte Black	 FMBR Matte Brass
 FMW Matte White				

Not seeing what you're looking for? Contact us to discuss more options.

