



MODEL #:	WATTAGE:	VOLTAGE:	KELVIN:	SIZE:
TECHNOLOGY:	ACCESSORIES:			
PROJECT:	NOTES:			
TYPE:	AREA:			

**FEATURES**


**PRODUCT IMAGE**

**APPLICATION**  
Ceiling  
Indoor

**LOCATION**  
Damp

**QUALITY FEATURES:**

- Fixture thermally tested to ensure longevity
- Maximum light distribution throughout lens
- Over current/voltage short circuit protection
- UL and/or CSA Compliant Listed



**LIGHT PROPERTIES**

**Available Kelvin Options:**



**LED CHIPS USED**  
LG/NICHIA/SAMSUNG

**TESTED**  
LM80 AND  
LM82

**CRI**  
80+

**LIFE HOURS**  
50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



**ASL LIGHTING**

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.  
© Copyright © 2020 ASL Lighting Inc. All rights reserved.



Approval upon request

# STANDARD OPTIONS

## STANDARD BASE CONSTRUCTION

CR Steel Construction






## STANDARD LENS

Smooth White Acrylic

## STANDARD FINISH

Brushed Nickel

## MODEL #HDT ORDER FORM











WATTAGE *	VOLTAGE	KELVIN	SIZE
W9 - 9	Standard Voltage: ND - 120V NON DIMMABLE	 27K	<b>D10</b> - D10 1/4 H3 3/8
W12 - 12		 30K	<b>D12</b> - D12 H3 3/8
W15 - 15	DV - 120V/277V NON DIMMABLE	 35K	<b>D14</b> - D14 1/2 H4
W20 - 20	TD - 120V TRIAC/ELV DIMMABLE	 40K	<b>D16</b> - D16 H4 3/8
W24 - 24	DVD - 120/277V 0-10V DIMMABLE	 50K	<b>D18</b> - D18 H4 3/8
W31 - 31			<b>D24</b> - D24 H5 <b>D31</b> - D31 H5 7/8 (Ova L)

\* Up to 200W available on fixtures over 24".

# SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control	FI - Finial

### CUSTOM FINISH OPTIONS

 FBG Gloss Black	 FBM Matte Black	 FBRG Gloss Brass	 FBRM Matte Brass	 FBZG Gloss Bronze
 FBZM Matte Bronze	 FCG Gloss Chrome	 FCM Matte Chrome	 FWG Gloss White	 FWM Matte White

Not seeing what you're looking for? Contact us to discuss more options.



## ASL LIGHTING

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2020 ASL Lighting Inc. All rights reserved.



Approval upon request