



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

- APPLICATION**
Ceiling
Indoor
- LOCATION**
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

3500K
NEUTRAL

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED
LG/NICHIA/SAMSUNG

TESTED
LM80 AND
LM82

CRI
80+

LIFE HOURS
50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
Marbleized Glass

STANDARD FINISH
Brushed Nickel

MODEL #TRCL ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W9 - 9	Standard Voltage: ND - 120V NON DIMMABLE	 27K	D15 - D15 H21
W12 - 12		 30K	D19 - D19 H22
W15 - 15	DV - 120V/277V NON DIMMABLE	 35K	
W20 - 20	TD - 120V TRIAC/ELV DIMMABLE	 40K	
W24 - 24	DVD - 120/277V 0-10V DIMMABLE	 50K	
W31 - 31			

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control	BB - Back Box (Extended Base) BBX - Back Box (Extended Base) (Conduit Holes Optional) CCS - Cable Cord Suspension System FI - Finial PK1 - Canopy/Pendant Kit/1 ROD PK2 - Canopy/Pendant Kit/2 RODS PK3 - Canopy/Pendant Kit/3 RODS

CUSTOM FINISH OPTIONS

Not seeing what you're looking for? Contact us to discuss more options.



ASL LIGHTING

725 East state St. Trenton,NJ 08609 | info@asllightng.com | www.asllighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2024 ASL Lighting Inc. All rights reserved.



Approval upon request