



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

- APPLICATION**
Indoor
Sconce
- LOCATION**
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

3500K
NEUTRAL

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED
LG/NICHIA/SAMSUNG

TESTED
LM80 AND
LM82

CRI
80+

LIFE HOURS
50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
Stainless Steel or Aluminum

STANDARD LENS
Smooth White Acrylic

STANDARD FINISH
Polished Aluminum

MODEL #BSLA ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W9 - 9 W12 - 12 W15 - 15 W20 - 20 W24 - 24 W31 - 31	Standard Voltage: ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE TD - 120V TRIAC/ELV DIMMABLE DVD - 120/277V 0-10V DIMMABLE	 27K  30K  35K  40K  50K	W4 - W4 1/4 H13 D3 1/4

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control	BB - Back Box (Extended Base) BBX - Back Box (Extended Base) (Conduit Holes Optional)

CUSTOM FINISH OPTIONS				
 AFBA Brushed Aluminum	 AFGBZ Gloss Bronze	 AFPC Polished Chrome	 AFSB Satin Brass	 FBZ Bronzestone
 FMB Matte Black	 FW White			

Not seeing what you're looking for? Contact us to discuss more options.

