

MODEL #

CCS27A

TECHNICAL SPECIFICATION



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

APPLICATION
Sconce Indoor

LOCATION
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

3500K
NEUTRAL

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED LG/NICHIA/SAMSUNG	TESTED LM80 AND LM82	CRI 80+	LIFE HOURS 50,000
--	--------------------------------	-------------------	-----------------------------

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
11	1276	1008
17	1972	1557
23	2668	2107
35	4060	3207
46	5336	4215

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
Clear on White Acrylic

STANDARD FINISH
Edge Trim, Brushed Nickel

MODEL #CCS27A ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W11 - 11	Standard Voltage: ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE TD - 120V TRIAC/ELV DIMMABLE DVD - 120/277V 0-10V DIMMABLE	 27K	H12 - H12 W8 D4
W17 - 17		 30K	
W23 - 23		 35K	
W35 - 35		 40K	
W46 - 46		 50K	

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming TP - Tamper Proof Screws	BB - Back Box (Extended Base) BBX - Back Box (Extended Base) (Conduit Holes Optional) FUS - Fused IB - Individually Boxed PS - Pin Switch

CUSTOM FINISH OPTIONS

Not seeing what you're looking for? Contact us to discuss more options.

