

MODEL #

CCS36B

TECHNICAL SPECIFICATION



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

- APPLICATION**
Indoor
Sconce
UP & DOWN
- LOCATION**
DAMP OR WET



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

3500K
NEUTRAL

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED
LG/NICHIA/SAMSUNG

TESTED
LM80 AND
LM82

CRI
80+

LIFE HOURS
50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
11	1276	1008
17	1972	1557
23	2668	2107
35	4060	3207
46	5336	4215

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
Stainless Steel or Aluminum

STANDARD LENS
Acrylic White

STANDARD FINISH
BLACK WITH BRASS ACCENTS

MODEL #CCS36B ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W11 - 11	Standard Voltage: ND - 120V NON DIMMABLE	 27K	H12 - H12 X W 4 X D4
W17 - 17		 30K	H16 - H16 X W4 X D4
W23 - 23	DV - 120V/277V NON DIMMABLE	 35K	H24 - H24 X W6 X D4
W35 - 35	TD - 120V TRIAC/ELV DIMMABLE	 40K	
W46 - 46	DVD - 120/277V 0-10V DIMMABLE	 50K	

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming TP - Tamper Proof Screws	BB - Back Box (Extended Base) BBX - Back Box (Extended Base) (Conduit Holes Optional) FUS - Fused IB - Individually Boxed PS - Pin Switch

CUSTOM FINISH OPTIONS

 AFBA Brushed Aluminum

 AFGBZ Gloss Bronze

 AFPC Polished Chrome

 AFSB Satin Brass

 FBZ Bronzestone

 FW White

Not seeing what you're looking for? Contact us to discuss more options.

