

MODEL #

# CCV40

TECHNICAL SPECIFICATION



|             |  |          |  |          |              |         |  |       |  |
|-------------|--|----------|--|----------|--------------|---------|--|-------|--|
| MODEL #:    |  | WATTAGE: |  | VOLTAGE: |              | KELVIN: |  | SIZE: |  |
| TECHNOLOGY: |  |          |  |          | ACCESSORIES: |         |  |       |  |
| PROJECT:    |  |          |  |          | NOTES:       |         |  |       |  |
| TYPE:       |  |          |  |          | AREA:        |         |  |       |  |

FEATURES

PRODUCT IMAGE

**APPLICATION**  
Indoor  
Over Bed & Vanity

**LOCATION**  
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K  
WARM WHITE

3000K  
SOFT WHITE

3500K  
NEUTRAL

4000K  
COOL WHITE

5000K  
DAYLIGHT

|                                            |                                   |                   |                             |
|--------------------------------------------|-----------------------------------|-------------------|-----------------------------|
| <b>LED CHIPS USED</b><br>LG/NICHIA/SAMSUNG | <b>TESTED</b><br>LM80 AND<br>LM82 | <b>CRI</b><br>80+ | <b>LIFE HOURS</b><br>50,000 |
|--------------------------------------------|-----------------------------------|-------------------|-----------------------------|

| WATTAGE | SOURCE LUMENS @40K | DELIVERED LUMENS |
|---------|--------------------|------------------|
| 11      | 1276               | 1008             |
| 17      | 1972               | 1557             |
| 23      | 2668               | 2107             |
| 35      | 4060               | 3207             |
| 46      | 5336               | 4215             |

| VOLTAGE                             |
|-------------------------------------|
| Standard:<br>ND - 120V NON DIMMABLE |
| DV - 120V/277V NON DIMMABLE         |
| TD - 120V TRIAC/ELV DIMMABLE        |
| DVD - 120/277V 0-10V DIMMABLE       |



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION  
Stainless Steel or Aluminum

STANDARD LENS  
White Acrylic

STANDARD FINISH  
Satin Nickel

MODEL #CCV40 ORDER FORM

| WATTAGE * | VOLTAGE                                                                                                                                         | KELVIN                                                                                | SIZE            |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-----------------|
| W11 - 11  | Standard Voltage:<br>ND - 120V NON DIMMABLE<br><br>DV - 120V/277V NON DIMMABLE<br>TD - 120V TRIAC/ELV DIMMABLE<br>DVD - 120/277V 0-10V DIMMABLE |  27K | L25 - L25 H4 D4 |
| W17 - 17  |                                                                                                                                                 |  30K | L37 - L37 H4 D4 |
| W23 - 23  |                                                                                                                                                 |  35K | L49 - L49 H4 D4 |
| W35 - 35  |                                                                                                                                                 |  40K |                 |
| W46 - 46  |                                                                                                                                                 |  50K |                 |

\* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

| TECHNOLOGY                                                                                                                        | ACCESSORIES                                                                                                                                                          |
|-----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EMG - Emergency<br>EMGR - Emergency Remote<br>OS - Occupancy Sensor<br>OSCD - Occupancy Sensor Step Dimming<br>PC - Photo Control | CO - Convenience Outlet<br>FBF - Front Baffle<br>FUS - Fused<br>NL - Night Light<br>PCH - Pull Chain<br>RS - Rocker Switch<br>TWS - Three Way Switching (Pull Chain) |

CUSTOM FINISH OPTIONS

-  FBZ Bronzestone
-  FMB Matte Black
-  FSN Satin Nickel
-  FW White

Not seeing what you're looking for? Contact us to discuss more options.



ASL LIGHTING

725 East state St. Trenton,NJ 08609 | info@asllightng.com | www.asllighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2024 ASL Lighting Inc. All rights reserved.



Approval upon request