

MODEL #

CNS-EMG

TECHNICAL SPECIFICATION



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:					ACCESSORIES:				
PROJECT:					NOTES:				
TYPE:					AREA:				

FEATURES

PRODUCT IMAGE

APPLICATION
Indoor
Sconce

LOCATION
Wet



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

3500K
NEUTRAL

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED LG/NICHIA/SAMSUNG	TESTED LM80 AND LM82	CRI 80+	LIFE HOURS 50,000
--	-----------------------------------	-------------------	-----------------------------

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION

Polycarbonate

STANDARD LENS

Clear Prismatic Polycarbonate

STANDARD FINISH

Bronzestone

MODEL #CNS-EMG ORDER FORM

WATTAGE	VOLTAGE	KELVIN	SIZE
W9 - 9 W12 - 12 W15 - 15 W20 - 20 W24 - 24 W31 - 31	Standard Voltage: ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE TD - 120V TRIAC/ELV DIMMABLE DVD - 120/277V 0-10V DIMMABLE	 27K  30K  35K  40K  50K	W6 - W6 H12 1/2 D2 3/4

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control

Not seeing what you're looking for? Contact us to discuss more options.

