



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:					ACCESSORIES:				
PROJECT:					NOTES:				
TYPE:					AREA:				

FEATURES

PRODUCT IMAGE


- APPLICATION

Indoor

Outdoor

Sconce
- LOCATION

Wet



LIGHT PROPERTIES

Available Kelvin Options:

2700K

WARM WHITE

3000K

SOFT WHITE

3500K

NEUTRAL

4000K

COOL WHITE

5000K

DAYLIGHT

LED CHIPS USED

LG/NICHIA/SAMSUNG

TESTED

LM80 AND LM82

CRI

80+

LIFE HOURS

50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
Polycarbonate

STANDARD LENS
Opal Polycarbonate

STANDARD FINISH
Black

MODEL #CRG ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W9 - 9	Standard Voltage: ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE TD - 120V TRIAC/ELV DIMMABLE DVD - 120/277V 0-10V DIMMABLE	 27K	W7 - W7 H10 1/4 D4
W12 - 12		 30K	
W15 - 15		 35K	
W20 - 20		 40K	
W24 - 24		 50K	
W31 - 31			

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control

Not seeing what you're looking for? Contact us to discuss more options.

