



| MODEL#: | WATTAGE: | VOLTAGE: | KELVIN: | SIZE: |
|-------------|----------|----------|--------------|-------|
| | | | | |
| TECHNOLOGY: | | | ACCESSORIES: | |
| PROJECT: | | | NOTES: | |
| TYPE: | | | AREA: | |
| | | | | |

FEATURES

PRODUCT IMAGE



APPLICATION

Indoor Outdoor Sconce



LOCATION











LIGHT PROPERTIES

Available Kelvin Options:





| WATTAGE | DELIVERED LUMENS | |
|---------|------------------|--|
| 9 | 400 | |

TESTED LM80 AND LM82 CRI 80+

LIFE HOURS 50,000

| VOI | ТΔ | GE |
|-----|----|----|

Standard:

ND - 120V NON DIMMABLE

DV - 120V/277V NON DIMMABLE





Cast Aluminum

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION

STANDARD LENS

Frosted Glass

STANDARD FINISH

Bronze

MODEL #CTWE ORDER FORM

| WATTAGE * | VOLTAGE | KELVIN | SIZE |
|---------------|---|------------------|----------------------------------|
| | | | |
| W9 - 9 | Standard Voltage: | ့ 30К | W6 - W6 1/2 H6 1/2 D3 1/2 |
| | ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE | 40K | |

* Up to 200W available on fixtures over 24".

Not seeing what you're looking for? Contact us to discuss more options.



