



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

APPLICATION
Outdoor
security

LOCATION
Wet



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

3500K
NEUTRAL

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED
LG/NICHIA/SAMSUNG

TESTED
LM80 AND
LM82

CRI
80+

LIFE HOURS
50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
Die Cast Aluminum

STANDARD LENS
Clear Glass

STANDARD FINISH
Bronzetone

MODEL #DSKQ ORDER FORM

WATTAGE	VOLTAGE	KELVIN	SIZE
W9 - 9	Standard Voltage: ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE TD - 120V TRIAC/ELV DIMMABLE DVD - 120/277V 0-10V DIMMABLE	 27K	H7 - H7 1/2 W14 1/2 D4 3/4
W12 - 12		 30K	
W15 - 15		 35K	
W20 - 20		 40K	
W24 - 24		 50K	
W31 - 31			

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY
EMG - Emergency OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for? Contact us to discuss more options.

