

MODEL #

# FAC

TECHNICAL SPECIFICATION



|             |  |          |  |          |  |              |  |       |  |
|-------------|--|----------|--|----------|--|--------------|--|-------|--|
| MODEL #:    |  | WATTAGE: |  | VOLTAGE: |  | KELVIN:      |  | SIZE: |  |
| TECHNOLOGY: |  |          |  |          |  | ACCESSORIES: |  |       |  |
| PROJECT:    |  |          |  |          |  | NOTES:       |  |       |  |
| TYPE:       |  |          |  |          |  | AREA:        |  |       |  |

FEATURES

PRODUCT IMAGE

**APPLICATION**  
Outdoor  
Sconce

**LOCATION**  
Wet



LIGHT PROPERTIES

Available Kelvin Options:

2700K  
WARM WHITE

3000K  
SOFT WHITE

3500K  
NEUTRAL

4000K  
COOL WHITE

5000K  
DAYLIGHT

|                                            |                                   |                   |                             |
|--------------------------------------------|-----------------------------------|-------------------|-----------------------------|
| <b>LED CHIPS USED</b><br>LG/NICHIA/SAMSUNG | <b>TESTED</b><br>LM80 AND<br>LM82 | <b>CRI</b><br>80+ | <b>LIFE HOURS</b><br>50,000 |
|--------------------------------------------|-----------------------------------|-------------------|-----------------------------|

| WATTAGE | SOURCE LUMENS @40K |
|---------|--------------------|
| 9       | 1259               |
| 12      | 1520               |
| 15      | 1750               |
| 20      | 2494               |

| VOLTAGE                                   |
|-------------------------------------------|
| Standard:<br>TD - 120V TRIAC/ELV DIMMABLE |
| ND - 120V NON DIMMABLE                    |
| DV - 120V/277V NON DIMMABLE               |



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION  
Polycarbonate

STANDARD LENS  
Acrylic

STANDARD FINISH  
Black

MODEL #FAC ORDER FORM

| WATTAGE * | VOLTAGE                                           | KELVIN                                                                                | SIZE          |
|-----------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------|
|           |                                                   |                                                                                       |               |
| W9 - 9    | Standard Voltage:<br>TD - 120V TRIAC/ELV DIMMABLE |  27K | D6 - D6 H8 W6 |
| W12 - 12  |                                                   |  30K |               |
| W15 - 15  | ND - 120V NON DIMMABLE                            |  35K |               |
| W20 - 20  | DV - 120V/277V NON DIMMABLE                       |  40K |               |
|           |                                                   |  50K |               |

\* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

| TECHNOLOGY                                                                          |
|-------------------------------------------------------------------------------------|
| OS - Occupancy Sensor<br>OSCD - Occupancy Sensor Step Dimming<br>PC - Photo Control |

Not seeing what you're looking for? Contact us to discuss more options.

