




|             |  |          |  |          |              |         |  |       |  |
|-------------|--|----------|--|----------|--------------|---------|--|-------|--|
| MODEL #:    |  | WATTAGE: |  | VOLTAGE: |              | KELVIN: |  | SIZE: |  |
| TECHNOLOGY: |  |          |  |          | ACCESSORIES: |         |  |       |  |
| PROJECT:    |  |          |  |          | NOTES:       |         |  |       |  |
| TYPE:       |  |          |  |          | AREA:        |         |  |       |  |

FEATURES

PRODUCT IMAGE

**APPLICATION**  
Indoor  
Sconce

**LOCATION**  
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K  
WARM WHITE

3000K  
SOFT WHITE

3500K  
NEUTRAL

4000K  
COOL WHITE

5000K  
DAYLIGHT

|                   |               |     |            |
|-------------------|---------------|-----|------------|
| LED CHIPS USED    | TESTED        | CRI | LIFE HOURS |
| LG/NICHIA/SAMSUNG | LM80 AND LM82 | 80+ | 50,000     |

| WATTAGE | SOURCE LUMENS @40K | DELIVERED LUMENS |
|---------|--------------------|------------------|
| 9       | 1259               | 1007             |
| 12      | 1520               | 1216             |
| 15      | 1750               | 1400             |
| 20      | 2494               | 1995             |
| 24      | 2793               | 2234             |
| 31      | 4000               | 3200             |

| VOLTAGE                             |
|-------------------------------------|
| Standard:<br>ND - 120V NON DIMMABLE |
| DV - 120V/277V NON DIMMABLE         |
| TD - 120V TRIAC/ELV DIMMABLE        |
| DVD - 120/277V 0-10V DIMMABLE       |



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION  
CR Steel Construction

STANDARD LENS  
Satin Nickel Accent

STANDARD FINISH  
Alabaster Glass

MODEL #GMK ORDER FORM

| WATTAGE *                                                          | VOLTAGE                                                                                                                                         | KELVIN                                                                                                                                                                                                                                                                                                                                                                                                                                                    | SIZE                   |
|--------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| W9 - 9<br>W12 - 12<br>W15 - 15<br>W20 - 20<br>W24 - 24<br>W31 - 31 | Standard Voltage:<br>ND - 120V NON DIMMABLE<br><br>DV - 120V/277V NON DIMMABLE<br>TD - 120V TRIAC/ELV DIMMABLE<br>DVD - 120/277V 0-10V DIMMABLE |  27K<br> 30K<br> 35K<br> 40K<br> 50K | W7 - W7 5/8 H11 D3 1/2 |

\* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

| TECHNOLOGY                                                                                                                        | ACCESSORIES                                                                              |
|-----------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| EMG - Emergency<br>EMGR - Emergency Remote<br>OS - Occupancy Sensor<br>OSCD - Occupancy Sensor Step Dimming<br>PC - Photo Control | BB - Back Box (Extended Base)<br>BBX - Back Box (Extended Base) (Conduit Holes Optional) |

| CUSTOM FINISH OPTIONS                                                                               |                                                                                                      |                                                                                                           |                                                                                                     |                                                                                                       |
|-----------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
|  FGB Gloss Black  |  FGBR Gloss Brass |  FGBZ Gloss Bronze     |  FGW Gloss White |  FMB Matte Black |
|  FMBR Matte Brass |  FMW Matte White  |  ORB Oil Rubbed Bronze |                                                                                                     |                                                                                                       |

Not seeing what you're looking for? Contact us to discuss more options.



ASL LIGHTING

725 East state St. Trenton,NJ 08609 | info@asllightng.com | www.asllighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609  
Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.  
© Copyright © 2024 ASL Lighting Inc. All rights reserved.



Approval upon request