




MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

APPLICATION
Ceiling
Indoor

LOCATION
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

3500K
NEUTRAL

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED	TESTED	CRI	LIFE HOURS
LG/NICHIA/SAMSUNG	LM80 AND LM82	80+	50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
Opal Glass & White Acrylic

STANDARD FINISH
Polished Chrome

MODEL #HDG ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W9 - 9	Standard Voltage: ND - 120V NON DIMMABLE	 27K	D12 - D12 (HEIGHT 4 OR 8)
W12 - 12		 30K	D15 - D15 (HEIGHT 4 OR 8)
W15 - 15	DV - 120V/277V NON DIMMABLE	 35K	D19 - D19 (HEIGHT 4 OR 8)
W20 - 20		 40K	D24 - D24 (HEIGHT 4 OR 8)
W24 - 24	TD - 120V TRIAC/ELV DIMMABLE	 50K	D30 - D30 (HEIGHT 4 OR 8)
W31 - 31	DVD - 120/277V 0-10V DIMMABLE		D42 - D42 (HEIGHT 4 OR 8)

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control	FI - Finial

CUSTOM FINISH OPTIONS

Not seeing what you're looking for? Contact us to discuss more options.

