



| | | | | |
|-------------|--------------|----------|---------|-------|
| MODEL #: | WATTAGE: | VOLTAGE: | KELVIN: | SIZE: |
| TECHNOLOGY: | ACCESSORIES: | | | |
| PROJECT: | NOTES: | | | |
| TYPE: | AREA: | | | |

FEATURES


PRODUCT IMAGE

APPLICATION
Ceiling
Indoor

LOCATION
Damp

QUALITY FEATURES:

- Fixture thermally tested to ensure longevity
- Maximum light distribution throughout lens
- Over current/voltage short circuit protection
- UL and/or CSA Compliant Listed



LIGHT PROPERTIES

Available Kelvin Options:



LED CHIPS USED
LG/NICHIA/SAMSUNG

TESTED
LM80 AND
LM82

CRI
80+

LIFE HOURS
50,000

| WATTAGE | SOURCE LUMENS @40K | DELIVERED LUMENS |
|---------|--------------------|------------------|
| 9 | 1259 | 1007 |
| 12 | 1520 | 1216 |
| 15 | 1750 | 1400 |
| 20 | 2494 | 1995 |
| 24 | 2793 | 2234 |
| 31 | 4000 | 3200 |

| VOLTAGE |
|-------------------------------------|
| Standard: ND - 120V NON DIMMABLE |
| DV - 120V/277V NON DIMMABLE |
| TD - 120V TRIAC/ELV DIMMABLE |
| DVD - 120/277V 0-10V DIMMABLE |



ASL LIGHTING

725 East state St. Trenton, NJ 08609 | info@aslighting.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.
© Copyright © 2020 ASL Lighting Inc. All rights reserved.



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION

CR Steel Construction






STANDARD LENS

Smooth White Acrylic

STANDARD FINISH

Brushed Nickel

MODEL #HDT ORDER FORM











| WATTAGE * | VOLTAGE | KELVIN | SIZE |
|-----------|---|---|--|
| W9 - 9 | Standard Voltage: ND - 120V NON DIMMABLE |  27K | D10 - D10 1/4 H3 3/8 |
| W12 - 12 | |  30K | D12 - D12 H3 3/8 |
| W15 - 15 | DV - 120V/277V NON DIMMABLE |  35K | D14 - D14 1/2 H4 |
| W20 - 20 | TD - 120V TRIAC/ELV DIMMABLE |  40K | D16 - D16 H4 3/8 |
| W24 - 24 | DVD - 120/277V 0-10V DIMMABLE |  50K | D18 - D18 H4 3/8 |
| W31 - 31 | | | D24 - D24 H5 D31 - D31 H5 7/8 (Ova L) |

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

| TECHNOLOGY | ACCESSORIES |
|---|-------------|
| EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control | FI - Finial |

CUSTOM FINISH OPTIONS

| | | | | |
|--|--|--|--|---|
|  FBG Gloss Black |  FBM Matte Black |  FBRG Gloss Brass |  FBRM Matte Brass |  FBZG Gloss Bronze |
|  FBZM Matte Bronze |  FCG Gloss Chrome |  FCM Matte Chrome |  FWG Gloss White |  FWM Matte White |

Not seeing what you're looking for? Contact us to discuss more options.



ASL LIGHTING

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2020 ASL Lighting Inc. All rights reserved.



Approval upon request