

MODEL #
HDTC

TECHNICAL SPECIFICATION



MODEL #:	WATTAGE:	VOLTAGE:	KELVIN:	SIZE:
TECHNOLOGY:	ACCESSORIES:			
PROJECT:	NOTES:			
TYPE:	AREA:			

FEATURES


PRODUCT IMAGE

APPLICATION
Ceiling
Indoor

LOCATION
Damp

QUALITY FEATURES:

- Fixture thermally tested to ensure longevity
- Maximum light distribution throughout lens
- Over current/voltage short circuit protection
- UL and/or CSA Compliant Listed



LIGHT PROPERTIES

Available Kelvin Options:



LED CHIPS USED
LG/NICHIA/SAMSUNG

TESTED
LM80 AND
LM82

CRI
80+

LIFE HOURS
50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



ASL LIGHTING

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.
© Copyright © 2020 ASL Lighting Inc. All rights reserved.



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION

CR Steel Construction






STANDARD LENS

Smooth White Acrylic

STANDARD FINISH

Brushed Nickel

MODEL #HDTC ORDER FORM











WATTAGE *	VOLTAGE	KELVIN	SIZE
W9 - 9	Standard Voltage: ND - 120V NON DIMMABLE	 27K	D10 - D10 1/4 H3 3/8
W12 - 12		 30K	D12 - D12 H3 3/8
W15 - 15	DV - 120V/277V NON DIMMABLE	 35K	D14 - D14 1/2 H4
W20 - 20	TD - 120V TRIAC/ELV DIMMABLE	 40K	D16 - D16 H4 3/8
W24 - 24	DVD - 120/277V 0-10V DIMMABLE	 50K	D18 - D18 H4 3/8
W31 - 31			D24 - D24 H5 D31 - D31 H5 7/8 (Ova L)

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control	FI - Finial PK1 - Canopy/Pendant Kit/1 ROD PK2 - Canopy/Pendant Kit/2 RODS PK3 - Canopy/Pendant Kit/3 RODS

CUSTOM FINISH OPTIONS

 FBG Gloss Black	 FBM Matte Black	 FBRG Gloss Brass	 FBRM Matte Brass	 FBZG Gloss Bronze
 FBZM Matte Bronze	 FCG Gloss Chrome	 FCM Matte Chrome	 FWG Gloss White	 FWM Matte White

Not seeing what you're looking for? Contact us to discuss more options.



ASL LIGHTING

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lightening representative.

© Copyright © 2020 ASL Lighting Inc. All rights reserved.



Approval upon request