

MODEL #

IMRC

TECHNICAL SPECIFICATION




MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

 **APPLICATION**
Ceiling/Sconce
Outdoor

 **LOCATION**
Wet



LIGHT PROPERTIES

Available Kelvin Options:

 2700K WARM WHITE	 3000K SOFT WHITE	 3500K NEUTRAL	 4000K COOL WHITE	 5000K DAYLIGHT
--	---	--	---	---

LED CHIPS USED LG/NICHIA/SAMSUNG	TESTED LM80 AND LM82	CRI 80+	LIFE HOURS 50,000
-------------------------------------	----------------------------	------------	----------------------

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
Polycarbonate

STANDARD LENS
Prismatic or White Polycarbonate

STANDARD FINISH
White

MODEL #IMRC ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W9 - 9	Standard Voltage: ND - 120V NON DIMMABLE	 27K	H7 - H7 W5 D5 1/2
W12 - 12		 30K	
W15 - 15	DV - 120V/277V NON DIMMABLE	 35K	
W20 - 20	TD - 120V TRIAC/ELV DIMMABLE	 40K	
	DVD - 120/277V 0-10V DIMMABLE	 50K	

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control	CCS - Cable Cord Suspension System PK1 - Canopy/Pendant Kit/1 ROD PK2 - Canopy/Pendant Kit/2 RODS PK3 - Canopy/Pendant Kit/3 RODS

Not seeing what you're looking for? Contact us to discuss more options.

