




|             |  |          |  |          |              |         |  |       |  |
|-------------|--|----------|--|----------|--------------|---------|--|-------|--|
| MODEL #:    |  | WATTAGE: |  | VOLTAGE: |              | KELVIN: |  | SIZE: |  |
| TECHNOLOGY: |  |          |  |          | ACCESSORIES: |         |  |       |  |
| PROJECT:    |  |          |  |          | NOTES:       |         |  |       |  |
| TYPE:       |  |          |  |          | AREA:        |         |  |       |  |

FEATURES

PRODUCT IMAGE

APPLICATION  
Bracket & Canopy  
Outdoor

LOCATION  
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K  
WARM WHITE

3000K  
SOFT WHITE

4000K  
COOL WHITE

5000K  
DAYLIGHT

CRI

80+

LIFE HOURS

50,000

LED GU24 BULB OR MEDIUM BULB

| LED BULB WATTAGE | SOURCE LUMENS @40K | DELIVERED LUMENS |
|------------------|--------------------|------------------|
| 6                | 600                | 450              |
| 9                | 900                | 675              |
| 12               | 1200               | 900              |

| VOLTAGE                                   |
|-------------------------------------------|
| Standard:<br>TD - 120V TRIAC/ELV DIMMABLE |
| ND - 120V NON DIMMABLE                    |
| DV - 120V/277V NON DIMMABLE               |



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION

Composite Construction

STANDARD LENS

Acrylic

STANDARD FINISH

Black or White

MODEL #LCL ORDER FORM

| WATTAGE  | VOLTAGE                                           | KELVIN                                                                                | SIZE                    |
|----------|---------------------------------------------------|---------------------------------------------------------------------------------------|-------------------------|
|          |                                                   |                                                                                       |                         |
| W6 - 6   | Standard Voltage:<br>TD - 120V TRIAC/ELV DIMMABLE |  27K | H13.5 - H13.5 X W8 X E8 |
| W9 - 9   |                                                   |  30K | H17.5 - H17.5 X W8 X E8 |
| W12 - 12 | ND - 120V NON DIMMABLE                            |  40K |                         |
|          | DV - 120V/277V NON DIMMABLE                       |  50K |                         |

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

| TECHNOLOGY                                  |
|---------------------------------------------|
|                                             |
| OS - Occupancy Sensor<br>PC - Photo Control |

Not seeing what you're looking for? Contact us to discuss more options.

