



Properties

|                   |                |
|-------------------|----------------|
| Base Construction | Steel          |
| Lens              | Acrylic        |
| Application       | Sconce         |
| Location          | Damp           |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

Standard Selection

|         |                    |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish  | Brushed Nickel     |
| CCT     | 3000K              |

Finish Options

|                |            |
|----------------|------------|
| Black          | Bronze     |
| Brushed Nickel | Gold/Brass |
| ORB            | White      |

CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

Options

| Size   | Dimensions                | Wattage  | Voltage   | Lumens         |
|--------|---------------------------|----------|---|----------------|
| ODF-11 | H:11.12" W:10.62" E:3.87" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DVD (120V-277V 0-10 dimming) | 1300/1950/2600 |

Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!  
[info@asllighting.com](mailto:info@asllighting.com)