



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:					ACCESSORIES:				
PROJECT:					NOTES:				
TYPE:					AREA:				

FEATURES

PRODUCT IMAGE

APPLICATION

Indoor
Sconce

LOCATION

Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

3500K
NEUTRAL

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED

LG/NICHIA/SAMSUNG

TESTED

LM80 AND
LM82

CRI

80+

LIFE HOURS

50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
9	1259	1007
12	1520	1216
15	1750	1400
20	2494	1995
24	2793	2234
31	4000	3200

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
Frosted Glass

STANDARD FINISH
Satin Nickel

MODEL #ODTA ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W9 - 9	Standard Voltage: ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE TD - 120V TRIAC/ELV DIMMABLE DVD - 120/277V 0-10V DIMMABLE	 27K	W16.5 - W16.5 X H9.8 D4
W12 - 12		 30K	
W15 - 15		 35K	
W20 - 20		 40K	
W24 - 24		 50K	
W31 - 31			

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control	BB - Back Box (Extended Base) BBX - Back Box (Extended Base) (Conduit Holes Optional)

CUSTOM FINISH OPTIONS				
 FGB Gloss Black	 FGBR Gloss Brass	 FGBZ Gloss Bronze	 FGW Gloss White	 FMB Matte Black
 FMBR Matte Brass	 FMW Matte White	 ORB Oil Rubbed Bronze		

Not seeing what you're looking for? Contact us to discuss more options.

