



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

APPLICATION

Ceiling

Outdoor

LOCATION

Wet



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

3500K
NEUTRAL

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED

LG/NICHIA/SAMSUNG

TESTED

LM80 AND LM82

CRI

80+

LIFE HOURS

50,000

WATTAGE			VOLTAGE		
			Standard:		
			ND - 120V NON DIMMABLE		
			DV - 120V/277V NON DIMMABLE		
			TD - 120V TRIAC/ELV DIMMABLE		
			DVD - 120/277V 0-10V DIMMABLE		

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
20	2494	1995
24	2793	2234
31	4000	3200
48	6200	4100

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
Die Cast Aluminum

STANDARD LENS
Clear Polycarbonate

STANDARD FINISH
Black

MODEL #RCSPB ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W20 - 20	Standard Voltage: ND - 120V NON DIMMABLE	 27K	L10.4 - L10.4 W10.4 H3.8
W24 - 24		 30K	
W31 - 31	DV - 120V/277V NON DIMMABLE	 35K	
W48 - 48	TD - 120V TRIAC/ELV DIMMABLE	 40K	
	DVD - 120/277V 0-10V DIMMABLE	 50K	

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY
EMG - Emergency OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming
CUSTOM FINISH OPTIONS

Not seeing what you're looking for? Contact us to discuss more options.

