

MODEL #

RFDS

TECHNICAL SPECIFICATION




MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

APPLICATION
Indoor
Mini Pendant LED Lamp

LOCATION
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED	TESTED	CRI	LIFE HOURS
LG/NICHIA/SAMSUNG	LM80 AND LM82	80+	50,000

LED GU24 BULB OR MEDIUM BULB

LED BULB WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
6	600	450
9	900	675
12	1200	900

VOLTAGE
Standard: TD - 120V TRIAC/ELV DIMMABLE
ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE



STANDARD OPTIONS

STANDARD BASE CONSTRUCTION

Stainless Steel or Aluminum

STANDARD FINISH

Black/Glod

White/Gold

White/White

MODEL #RFDS ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W6 - 6 W9 - 9 W12 - 12	Standard Voltage: TD - 120V TRIAC/ELV DIMMABLE ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE	 27K  30K  40K  50K	D6 - D6 H8 D8 - D8 1/2 H16 1/2

** Up to 200W available on fixtures over 24".*

CUSTOM FINISH OPTIONS

 AFBA Brushed Aluminum

 AFGBZ Gloss Bronze

 AFPC Polished Chrome

 AFSB Satin Brass

 FBZ Bronzestone

 FMB Matte Black

 FW White

Not seeing what you're looking for? Contact us to discuss more options.

