



MODEL #:		WATTAGE:		VOLTAGE:		KELVIN:		SIZE:	
TECHNOLOGY:						ACCESSORIES:			
PROJECT:						NOTES:			
TYPE:						AREA:			

FEATURES

PRODUCT IMAGE

APPLICATION
Ceiling Indoor
Mini Pendant

LOCATION
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K
WARM WHITE

3000K
SOFT WHITE

4000K
COOL WHITE

5000K
DAYLIGHT

LED CHIPS USED	TESTED	CRI	LIFE HOURS
LG/NICHIA/SAMSUNG	LM80 AND LM82	80+	50,000

E26 FILAMENT LED BULB,

LED BULB WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
6	600	450
9	900	675
12	1200	900

VOLTAGE
Standard: TD - 120V TRIAC/ELV DIMMABLE
ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION
CR Steel Construction

STANDARD LENS
Clear Glass

STANDARD FINISH
Satin Nickel

MODEL #RFHQ ORDER FORM

WATTAGE *	VOLTAGE	KELVIN	SIZE
W6 - 6 W9 - 9 W12 - 12	Standard Voltage: TD - 120V TRIAC/ELV DIMMABLE ND - 120V NON DIMMABLE DV - 120V/277V NON DIMMABLE	 27K  30K  40K  50K	W5.8 - W5.8 H7.6 xH2 6'

* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

ACCESSORIES
BB - Back Box (Extended Base) BBX - Back Box (Extended Base) (Conduit Holes Optional) CCS - Cable Cord Suspension System PK1 - Canopy/Pendant Kit/1 ROD PK2 - Canopy/Pendant Kit/2 RODS PK3 - Canopy/Pendant Kit/3 RODS
CUSTOM FINISH OPTIONS
 FGB Gloss Black  FGBR Gloss Brass  FGBZ Gloss Bronze  FGW Gloss White  FMB Matte Black  FMBR Matte Brass  FMW Matte White  ORB Oil Rubbed Bronze

Not seeing what you're looking for? Contact us to discuss more options.

