



|             |  |          |  |          |  |              |  |       |  |
|-------------|--|----------|--|----------|--|--------------|--|-------|--|
| MODEL #:    |  | WATTAGE: |  | VOLTAGE: |  | KELVIN:      |  | SIZE: |  |
| TECHNOLOGY: |  |          |  |          |  | ACCESSORIES: |  |       |  |
| PROJECT:    |  |          |  |          |  | NOTES:       |  |       |  |
| TYPE:       |  |          |  |          |  | AREA:        |  |       |  |

FEATURES

PRODUCT IMAGE

APPLICATION  
Ceiling  
Indoor

LOCATION  
Damp



LIGHT PROPERTIES

Available Kelvin Options:

2700K  
WARM WHITE

3000K  
SOFT WHITE

3500K  
NEUTRAL

4000K  
COOL WHITE

5000K  
DAYLIGHT

LED CHIPS USED  
LG/NICHIA/SAMSUNG

TESTED  
LM80 AND  
LM82

CRI  
80+

LIFE HOURS  
50,000

| WATTAGE | SOURCE LUMENS @40K | DELIVERED LUMENS |
|---------|--------------------|------------------|
| 9       | 1259               | 1007             |
| 12      | 1520               | 1216             |
| 15      | 1750               | 1400             |
| 20      | 2494               | 1995             |
| 24      | 2793               | 2234             |
| 31      | 4000               | 3200             |

| VOLTAGE                             |
|-------------------------------------|
| Standard:<br>ND - 120V NON DIMMABLE |
| DV - 120V/277V NON DIMMABLE         |
| TD - 120V TRIAC/ELV DIMMABLE        |
| DVD - 120/277V 0-10V DIMMABLE       |



Approval upon request

STANDARD OPTIONS

STANDARD BASE CONSTRUCTION  
CR Steel Construction

STANDARD LENS  
Satin White

STANDARD FINISH  
Chocolate Linen

MODEL #RFOC ORDER FORM

| WATTAGE * | VOLTAGE                                     | KELVIN                                                                                | SIZE             |
|-----------|---------------------------------------------|---------------------------------------------------------------------------------------|------------------|
| W9 - 9    | Standard Voltage:<br>ND - 120V NON DIMMABLE |  27K | L24 - L24 W15 H6 |
| W12 - 12  |                                             |  30K | L36 - L36 W15 H6 |
| W15 - 15  | DV - 120V/277V NON DIMMABLE                 |  35K | L48 - L48 W15 H6 |
| W20 - 20  | TD - 120V TRIAC/ELV DIMMABLE                |  40K |                  |
| W24 - 24  | DVD - 120/277V 0-10V DIMMABLE               |  50K |                  |
| W31 - 31  |                                             |                                                                                       |                  |

\* Up to 200W available on fixtures over 24".

SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

| TECHNOLOGY                                                                                                                        | ACCESSORIES                                                                                                                                                                                                                                           |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EMG - Emergency<br>EMGR - Emergency Remote<br>OS - Occupancy Sensor<br>OSCD - Occupancy Sensor Step Dimming<br>PC - Photo Control | BB - Back Box (Extended Base)<br>BBX - Back Box (Extended Base) (Conduit Holes Optional)<br>CCS - Cable Cord Suspension System<br>FI - Finial<br>PK1 - Canopy/Pendant Kit/1 ROD<br>PK2 - Canopy/Pendant Kit/2 RODS<br>PK3 - Canopy/Pendant Kit/3 RODS |

CUSTOM FINISH OPTIONS

LENS OPTIONS



LJL-JUTE LINEN



LR-RAPIDS



LWL-WHITE LINEN

Not seeing what you're looking for? Contact us to discuss more options.



ASL LIGHTING

725 East state St. Trenton,NJ 08609 | info@asllightng.com | www.asllighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609  
Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.  
© Copyright © 2024 ASL Lighting Inc. All rights reserved.



Approval upon request